

GT2 400°F



The GT2 flexible hose has a structure made of armoured tissue vulcanised inside out with high temperature EPDM rubber achieving an operating temperature range of -40°F to + 400°F. The hose is totally crushproof thanks to the nylon helix which is keeping the structure opened also during stressing tests. The internal smooth and lubricated surface let the gas easily flow and block the acid aggression of the toxic gases preserving the long life of the product.

GT2	Ø	L.
GT2-752	3"	8'
GT2-755	3"	16'
GT2-757	3"	25'
GT2-7510	3"	33'
GT2-7512	3"	41'
GT2-7515	3"	49'
GT2-7520	3"	66'
GT2-7540	3"	131'

GT2	Ø	L.
GT2-1002	4"	8'
GT2-1005	4"	16'
GT2-1007	4"	25'
GT2-10010	4"	33'
GT2-10012	4"	41'
GT2-10015	4"	49'
GT2-10020	4"	66'
GT2-10040	4"	131'

GT2	Ø	L.
GT2-1252	5"	8'
GT2-1255	5"	16'
GT2-1257	5"	25'
GT2-12510	5"	33'
GT2-12512	5"	41'
GT2-12515	5"	49'
GT2-12520	5"	66'

GT2	Ø	L.
GT2-1502	6"	8'
GT2-1505	6"	16'
GT2-1507	6"	25'
GT2-15010	6"	33'
GT2-150120	6"	41'
GT2-150152	6"	49'
GT2-15020	6"	66'

GT2	Ø	L.
GT2-2005	8"	16'
GT2-20010	8"	33'
GT2-20015	8"	66'



Flexible hose made of one aluminized coated fiberglass fabric sewn with one silicone coated both sides by glass fabric, external metal wire sewn with yellow high temperature resistant scuffstrip onto the wall. Each end is reinforced with helix-free cuffs and the hoses should not be cut in order to maintain the fire-proof performances.

GT3  600°F

GT3	Ø	L.
GT3-1002	4"	8'
GT3-1005	4"	16'
GT3-1007	4"	25'
GT3-10010	4"	33'
GT3-1252	5"	8'
GT3-1255	5"	16'
GT3-1257	5"	25'
GT3-12510	5"	33'
GT3-1502	6"	8'
GT3-1505	6"	16'
GT3-1507	6"	25'
GT3-15010	6"	33'
GT3-2002	8"	8'
GT3-2005	8"	16'
GT3-2007	8"	25'
GT3-20010	8"	33'

GT5  950°F

GT5	Ø	L.
GT5-1002	4"	8'
GT5-1005	4"	16'
GT5-1007	4"	25'
GT5-10010	4"	33'
GT5-1252	5"	8'
GT5-1255	5"	16'
GT5-1257	5"	25'
GT5-12510	5"	33'
GT5-1502	6"	8'
GT5-1505	6"	16'
GT5-1507	6"	25'
GT5-15010	6"	33'
GT5-2002	8"	8'
GT5-2005	8"	16'
GT5-2007	8"	25'
GT5-20010	8"	33'

GT7  1300°F

GT7	Ø	L.
GT7-1002	4"	8'
GT7-1005	4"	16'
GT7-1007	4"	25'
GT7-10010	4"	33'
GT7-1252	5"	8'
GT7-1255	5"	16'
GT7-1257	5"	25'
GT7-12510	5"	33'
GT7-1502	6"	8'
GT7-1505	6"	16'
GT7-1507	6"	25'
GT7-15010	6"	33'
GT7-2002	8"	8'
GT7-2005	8"	16'
GT7-2007	8"	25'
GT7-20010	8"	33'

GT1  1850°F

GT1	Ø	L.
GT1-1002	4"	8'
GT1-1005	4"	16'
GT1-1007	4"	25'
GT1-10010	4"	33'
GT1-1252	5"	8'
GT1-1255	5"	16'
GT1-1257	5"	25'
GT1-12510	5"	33'
GT1-1502	6"	8'
GT1-1505	6"	16'
GT1-1507	6"	25'
GT1-15010	6"	33'
GT1-2002	8"	8'
GT1-2005	8"	16'
GT1-2007	8"	25'
GT1-20010	8"	33'



GTA



Rugged aluminum hose resistant up to 600° F and extensible from 3' to 10' of total length. Suitable for connecting the hose reels to rigid piping.

GTA	Ø
GTA-100	4"
GTA-120	4.7"
GTA-130	5.1"
GTA-150	6"

GTA	Ø
GTA-160	6.3"
GTA-180	7"
GTA-200	8"
GTA-250	10'

GTP



Flexible hose up to 230°F made of PVC-coated polyamide fabric on both sides and built-in spiral wire of harmonic steel.

GTP	Ø	L.
GTP-100	4"	33'
GTP-125	5"	33'
GTP-130	5.1"	33'
GTP-150	6"	33'

GTP	Ø	L.
GTP-160	6.3"	33'
GTP-200	8"	33'
GTP-250	10"	33'
GTP-300	12"	33'

GCC



Metal cowling for flexible hose connection.

GCC	Ø
GCC-75	3"
GCC-100	4"
GCC-125	5"
GCC-150	6"
GCC-200	8"

GWB



Wall storage bracket for flexible hoses and Y pieces with nozzles.

GWB	Ø of suitable hoses
GWB-100	3" - 4"
GWB-125	5" - 6"

GF



Metallic hose clamp suitable to fix flexible hoses on cowlings or nozzles.

GF	Ø
GF-75	3"
GF-100	4"
GF-125	5"
GF-130	5.1"
GF-150	6"

GF	Ø
GF-160	6.3"
GF-200	8"
GF-250	10"
GF-315	12"

GSR



Bayonet quick connection coupling for flexible hoses. The code comprehends both the male and the female part

GSR	Ø
GSR-75	3"
GSR-100	4"
GSR-125	5"
GSR-150	6"
GSR-200	8"

GY



Symmetrical Y piece with 2 hoses GT2 4' long each, female quick coupling and hose clamps.

GY	ØA	ØB	ØC
GY-757575	3"	3"	3"
GY-1007575	4"	3"	3"
GY-100100100	4"	4"	4"
GY-125100100	5"	4"	4"
GY-150100100	6"	4"	4"
GY-150125125	6"	5"	5"

GYG



Symmetrical Y piece suitable for a quick connection to the GRNG nozzle, two hoses GT2 4' long each and hose clamps.

GYG	Ø	Lenght
GYG-1007575	3"	2 x 4'
GYG-100100100	4"	2 x 4'

GYOG



Symmetrical Y piece suitable for a quick connection to the GON oval nozzle, two hoses GT2 4' long each and hose clamps.

GYOG	Ø A	Ø B	Lenght
GYOG-7575	3"	3"	2 x 4'
GYOG-100100	4"	4"	2 x 4'

GDY



Symmetrical Y piece with anti-slip edging for flexible hoses and female part of quick coupling integrated.

GDY	Ø A	Ø B	Ø C
GDY-757575	3"	3"	3"
GDY-1007575	4"	4"	4"
GDY-100100100	4"	4"	4"
GDY-1257575	5"	3"	3"

GDY	Ø A	Ø B	Ø C
GDY-125100100	5"	4"	4"
GDY-125125125	5"	5"	5"
GDY-150125125	6"	5"	5"
GDY-150150150	6"	6"	6"

GDYG



Symmetrical Y piece suitable for a quick connection to the GRNG nozzle.

GDYG	Ø A	Ø B	Ø C
GDYG-1007575	4"	3"	3"
GDYG-100100100	4"	4"	4"

GDYOG



Symmetrical Y piece suitable for a quick connection to the GON nozzle.

GDYOG	Ø A	Ø B
GDYOG-7575	3"	3"
GDYOG-100100	4"	4"